

## **Technical Specification**



Product Code: VPSC722BK **Description:** 20A Ingot Double Pole Plate Switch





Insert & Housing: Urea

Earth Strap: Mild Steel

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

## **General Information**

Plate Dimensions (mm) 88 (W) x 88 (H) x 8 (D)

Dimensions With Gasket (mm) 91 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 60.3

> Victorian Finish Satin Chrome

Insert Colour Black Gasket Colour Black

Materials Front Plate: Stainless Steel

Switch Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 20 Termination Type Screw

> Terminal Size (mm) Ø5 Terminal Torque Value (Nm) 1.8

Terminal Capacity - Solid (mm²) 3 x 2.5

Double Pole Switch Yes Twin Earth Terminals Yes

Minimum Back Box Depth (mm)

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

> Warranty (Years) 10

**Standards** BS EN 60669-1: 2018

Additional Information

Scolmore House, Mariner, Lichfield Road Industrial Estate,

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.