

## **Technical Specification**



Product Code: VPSC535BK **Description:** 13A Ingot 1 Gang Double Pole Switched Socket Outlet





Insert & Housing: Urea

Earth Strap: Mild Steel

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

## **General Information**

Dimensions 88mm (W) x 88mm (H) x 8mm (D)

**Dimensions With Gasket** 91mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Satin Chrome

Insert & Gasket Colour Black

> Materials Front Plate: Stainless Steel

> > Switch Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

> Load Rating 13A

Plate Fixing Centres 60.3mm

Terminal Size 5mmø **Terminal Torque** 2.5Nm

**Terminal Capacity** 3 x 2.5mm<sup>2</sup> or 2 x 4mm<sup>2</sup>

Double Pole Yes

Ingress Protection

**Back Box Depth** 25mm Minimum

**Termination Type** Screw

**Operational Temperature** -5°C to +40°C

> Warranty 10 Years

**Standards** BS 1363-2: 2016 +A1: 2018

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

UK Design Registration: 3015621

**Additional Information**