

Technical Specification



Product Code: VPSS536BK Description: 13A Ingot 2 Gang Double Pole Switched Socket Outlet





Insert & Housing: Urea

Earth Strap: Mild Steel

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm) 2

General Information

Plate Dimensions (mm) 146 (W) \times 88 (H) \times 8 (D)

Dimensions With Gasket (mm) 149 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

Style Victorian
Finish Stainless Steel

Insert Colour Black

Gasket Colour Black

Materials Front Plate: Stainless Steel
Switch Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated

lettiina Sciews. Steel & fellow Passivated

Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250 Frequency (Hz) 50

Resistive Load Rating (A) 13

Termination Type Screw

Terminal Size (mm) Ø5
Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Yes

Twin Earth Terminals Yes

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years) 10

Standards BS 1363-2: 2016 +A1: 2018

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

