

# Technical Specification

**Product Code:** MD047BKSC

**Description:** 13A Ingot Fused Connection Module



## General Information

<b>Dimensions (mm)</b>	25 (W) x 57 (H) x 25.2 (D)	
<b>Finish</b>	Satin Chrome	
<b>Insert Colour</b>	Black	
<b>Materials</b>	Cover & Fuse Drawer: Nylon Drawer Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated	Rear Housing: Nylon Terminals: Brass Internal Busbars: Formed Pressed Brass
<b>Rated Voltage (V~) (Ue)</b>	250	<b>Frequency (Hz)</b> 50
<b>Resistive Load Rating (A)</b>	13	
<b>Fuse Fitted Rating &amp; Type</b>	13A (BS 1362)	
<b>Termination Type</b>	Screw	
<b>Terminal Size (mm)</b>	Ø3.5	<b>Terminal Torque Value (Nm)</b> 0.5
<b>Terminal Capacity - Solid (mm²)</b>	4 x 1.5 or 2 x 2.5	
<b>Modular Rocker Switches</b>	Yes	
<b>Product Marking</b>	Fused Symbol	
<b>Minimum Back Box Depth (mm)</b>	25 (35 Flat Plate)	
<b>Operational Temperature (°C)</b>	-5 to +40	
<b>Warranty (Years)</b>	10	
<b>Standards</b>	BS 5733: 2010 +A1: 2014 BS 1362: 1973 +A3: 2021	

**Additional Information** Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.