

Product Code: MM022WH

Luckinslive 391865608

Description: 20A Double Pole Switch Module



General Information

Dimensions (mm)	25 (W) x 50 (H) x 22 (D)		
Colour	Polar White		
Materials	Switch:	Urea	
	Terminal Screws:	Steel & Yellow Passivated	Terminals: Brass
	Internal Busbars:	Formed Pressed Brass	Contacts: Silver "on-lay" Copper / Brass
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	20		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2.5
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4		
Modular Rocker Switches	Yes		
Double Pole Switch	Yes		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	2		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



CLICK OR SCAN

Catalogue



Range



DoC



CLICK OR SCAN