

## **Technical Specification**



Product Code: SIN036PW

Description: 13A 2 Gang Double Pole Switched Socket Outlet Insert



General Information		
Insert Dimensions (mm)	142.5 (W) x 82.5 (H) x 2.5 (D)	
Plate Fixing Centres - Horizontal (mm)	120.6	
Style	Screwless Insert	
Insert Colour	Polar White	
Compatible Cover Plate	SCP436#	
Materials	Insert: Polycarbonate	Rear Housing: Urea
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars: Formed Pressed Brass
	Earth Strap: Mild Steel	
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5 Termir	nal Torque Value (Nm) 2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5 or 2 x 4	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Minimum Back Box Depth (mm)	35	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards BS 136	3-2: 2016 +A1: 2018	
diagran	that the mains supply is isolated before common with the relevant product.	encing installation and refer to the circuit priate sleeving and wired to the earth terminal.

CECK

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 1 of 2 (29/10/21) Errors & Omissions excluded. Specification is subject to change without notice.



## **Technical Specification**



5 (W) x 86 (H) x 4 (D) (Brushed Stainless), CH (Polished Chrome), SS (St ick), PW (Polar White) & RD (Red) corative & Metal Black or White: Stainless Steel, Bla	
(Brushed Stainless), CH (Polished Chrome), SS (St ick), PW (Polar White) & RD (Red)	
uck), PW (Polar White) & RD (Red)	
corative & Metal Black or White: Stainless Steel, Bla	ack, Polar White & Red: Polycarbonate
SCP436CH	SCP436SS
SCP436BK	SCP436PW

SCP436RD

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com UK Design Registration: 3015621

Page 2 of 2 (29/10/21) Errors & Omissions excluded. Specification is subject to change without notice.