

Product Code: MM047WH

Luckinslive 392590655

Description: 13A Fused Connection Module



**General Information**

Dimensions (mm)	25 (W) x 50 (H) x 24.7 (D)		
Colour	Polar White		
Materials	Cover & Housing: Polycarbonate	Terminals: Brass	
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars: Formed Pressed Brass	
Anti Microbial Certified	No		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Fuse Fitted Type	Plug Top Cartridge Fuse		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.8
Terminal Capacity - Solid (mm²)	4 x 1.5 or 3 x 2.5		
Product Marking	Fused Symbol		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	2		

**Standards** BS 1363-4, BS 1362

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

