

ELU56

7 Day 16 Amp Electronic Time Controller

Features & Benefits

- 72 × 72mm plug-in base surface mount
- 112 memory locations – 56 different ON/OFF operations per week
- Self-cancelling override on the 3rd subsequent programme change
- Shortest switching time 1 minute
- Programme suspension
- 1000 hours rechargeable memory back-up
- Optional panel mount (clip included)
- Can be mounted in 68mm square panel hole with aid of mounting bracket AK305 supplied
- They can also be mounted on DIN rail using adaptor 907-0-071



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount, Panel Mount (68mm), Din-rail Mount (3 Wire)
Earth Class Rating	Class II
Operating Temperature	-10°C to +40°C
Setting Type	Digital
Battery Type	NiCd 1.2V Rechargeable Battery (Non Replaceable)

Data sheet

ELU56

Time / Trade Time Controllers

Power Reserve	1000 Hours
Program Modes	24 Hour/7 Day
Switch type	Single Pole
Voltage Free Contacts	Normally Open
Mounting Hole Centres (mm)	57
Standby Consumption	<1W
Number of Channels	1
Switch rating	16A Resistive 5A Inductive, 80W LED
Shortest Switching Time	1 Minute
Programmable Slots	8 ON, 8 OFF
Permanent ON Facility	Yes (Until next programme change)
Cable Entry(s)	x3 Knock Out Holes Via Base Plate Cover, Back Entry

General

Weight (g)	196
Height (mm)	104
Width (mm)	72
Depth (mm)	69
Body Construction	Polycarbonate
Product Colour	Grey
Accessories (Included)	Screws / Plastic Cover / AK305 (Panel Mounting Bracket)
Accessories (Optional)	907.0.071 (DIN-rail Adapter) Sold separately
EAN Number	5012483004951
Guarantee Period	3 Years

Line Diagrams

