SLW2400

2000W PIR Light Controller - White

Features & Benefits

- IP44 weatherproof rating
- Adjustable light ON time
- Manual override
- Hinged back box for ease of wiring

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP44
Setting Type	Dial
Max Mounting Height (Mtr)	2.5
Motion Detection (Mtr)	12
Detection Angle	180°
Pan & Tilt Adjustment	90° Tilt Up/Down From Centre
Mounting Hole Centres (mm)	68
Standby Consumption	<0.5W

TIMEGUARD®
A **theben** Group Company

additional information at:
https://www.timeguard.com

This data was generated on

17/05/2022

Subject to technical changes and misprints

Number of Channels	1
Switch rating	2000W Halogen, 500W Fluorescent
ON Time Adjustment	5 Seconds to 18 Minutes. User Adjustable
Lux Level	20 to 1000
Detection Range (Mtr)	12
Permanent ON Facility	Yes (Pulse Override)
Cable Entry(s)	Back Entry

General

Weight (g)	200
Height (mm)	64
Width (mm)	86
Depth (mm)	119
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483008942
Guarantee Period	3 Years

TIMEGUARD®
A theben Group Company

additional information at:
https://www.timeguard.com

This data was generated on

17/05/2022

Subject to technical changes and misprints

Line Diagrams

TIMEGUARD®

A **theben** Group Company

Subject to technical changes and misprints

additional information at:
https://www.timeguard.com

This data was generated on

17/05/2022