

MTLW3000

Night Eye PIR Light Controller

Features & Benefits

- Adjustable Light Level Control
- IP55 Weatherproof Rating
- Adjustable Light ON Time
- Manual ON/OFF Override
- Hinged Back Box for Ease of Wiring



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP55
Setting Type	Dial
Max Mounting Height (Mtr)	2.5
Motion Detection (Mtr)	12
Detection Angle	200°
Pan & Tilt Adjustment	90° Tilt Up/Down From Centre
Mounting Hole Centres (mm)	68
Standby Consumption	<1.1W

Data sheet

MTLW3000

Light / PIR Lighting Controllers

Number of Channels	1
Switch rating	140W LED, 2300W Halogen, 500W Fluorescent/Low Energy Lighting
ON Time Adjustment	5 Seconds to 18 Minutes
Lux Level	20 to 1000
Detection Range (Mtr)	12
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Yes
Cable Entry(s)	Back Entry

General

Weight (g)	200
Height (mm)	64
Width (mm)	86
Depth (mm)	119
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483010938
Guarantee Period	5 Years

Data sheet

MTLW3000

Light / PIR Lighting Controllers

Line Diagrams

