

TGBT6

Boostmaster 2 Hour Plug-In Electronic Boost Timer

Features & Benefits

- Multiple boost times to choose from.
- Easy to use push button control.
- Boost times illuminated to track the time remaining before switching off.
- ON time can be increased in 4 steps: 0.25, 0.50, 1 and 2 hours.



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Plug-in
Earth Class Rating	Class I
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Setting Type	Button Press
Push Buttons	Yes (Boost Button)
Switch type	Single Pole
Standby Consumption	<1W
Switch rating	13A Resistive, 100W LED, 1000W Halogen, 500W Fluorescent

Data sheet

TGBT6

Time / Immersion & General Purpose Timeswitches

Shortest Switching Time	15 Minutes
Time Delay Range	15 Minutes to 2 Hours (¼ Hour, ½ Hour, 1 Hour and 2 Hours)
Permanent ON Facility	No

General

Weight (g)	123
Height (mm)	102
Width (mm)	55
Depth (mm)	46
Body Construction	Polycarbonate
Product Colour	White
EAN Number	5012483011393
Guarantee Period	3 Years

Data sheet

TGBT6

Time / Immersion & General Purpose Timeswitches

Line Diagrams

