

Data sheet

NTT01

Time / Immersion & General Purpose Timeswitches

NTT01

24 Hour Compact Immersion Heater Timeswitch

Features & Benefits

- 96 Quick-Set Segments for up to 48 ON/48 OFF Programmes Per 24 Hrs
- Red LED 'Mains ON' and Green LED 'Output' Indicators For Easy Viewing
- 'Traffic Light' Slide Switch for Easy ON (green), Auto (green & red) and OFF (red) Mode Indication
- Switches ON and OFF at Preset Times
- Easy to Use Captive Segment Dial
- Permanent ON/OFF Control
- Fits a Standard Flush or Surface Mount Box min 32mm



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Setting Type	Segment
Back Box Minimum Depth (mm)	32

Data sheet

NTT01

Time / Immersion & General Purpose Timeswitches

Program Modes	24 Hour
Switch type	Single Pole
Mounting Hole Centres (mm)	60
Standby Consumption	<1.43W
Number of Channels	1
Switch rating	16A Resistive 6A Inductive, 100W LED
Shortest Switching Time	15 Minutes
Programmable Slots	48 ON 48 OFF (96 Segments)
Permanent ON Facility	Yes (Slider Switch)
Cable Capacity (mm²)	1.5 - 2.5mm ² Flexible Cable
Cable Entry(s)	Back Entry

General

Weight (g)	160
Height (mm)	92
Width (mm)	92
Depth (mm)	60
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483012291
Guarantee Period	3 Years

Data sheet

NTT01

Time / Immersion & General Purpose Timeswitches

Line Diagrams

