

DS4

Pneumatic Time Delay Switch



Features & Benefits

- Replaces existing single gang wall switch
- Ideal for staircases and corridors
- Variable delay times
- Single pole/neutral not required
- Compatible with 20mm back boxes

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush Wall Box / Surface Mount Patress Box
Earth Class Rating	Class II
Operating Temperature	-10°C to +40°C
Ingress Protection Rating	IP20
Connection	2-Wire
Back Box Minimum Depth (mm)	20
Push Buttons	Push To Make
Switch type	Single Pole
Standby Consumption	<0W
Number of Channels	1

Data sheet

DS4

Light / Automatic Light Switches

Switch rating	1.4kW (Resistive) Filament Lamps, 700W Fluorescent, 3A Inductive loads, 80W LED. The LED switching capabilities of this product can be increased up to 200W by the addition of the Timeguard ZV900 Automatic Switch Load Controller. The ZV900 is sold separately
Time Delay Range	10 Seconds to 10 Minutes, User Adjustable (via a tamper-proof timing screw)
Multiple Unit Support	3 DS4 Units Max (wired in parallel to control the same load).
Cable Entry(s)	Back Entry

General

Weight (g)	81
Height (mm)	82
Width (mm)	82
Depth (mm)	40
Protruding Depth (mm)	36
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Screws / Caps
Accessories (Optional)	ZV900 Automatic Switch Load Controller. (Sold separately)
EAN Number	5012483012284
Guarantee Period	3 Years

Line Diagrams

