

## SN 5 SL GB

SMALL WATER HEATERS 5 TO 15 L

PRODUCT-NO.: 221125

The SN small water heater is designed to supply one draw-off point and is mounted over the sink. The appliances can be adjusted to anywhere between 35 °C and 85 °C, making water with a consistent temperature available at all times. The high limit safety cut-out provides a constant and safe maximum water temperature. As an option, this can be set to 38 °C, 45 °C, 55 °C or 65 °C. The highly effective thermal insulation used in the small water heaters minimises energy losses.



### The main features

Small water heater, 5 litre capacity

---

For a single draw-off point

---

Extremely large amount of mixed water

---

Low standby loss power consumption

---

Economy setting 60 °C

---

Splashproof to IP 24

---

Power cable for permanent connection, approx. 1 m



Type	SN 5 SL GB	SN 10 SL GB	SN 15 SL GB
Part no.	221125	222192	227682
Connected load	2 kW	2 kW	3,3 kW
Width	263 mm	295 mm	316 mm
Depth	230 mm	275 mm	295 mm
Height	420 mm	503 mm	601 mm

## Technical data

Rated voltage 1	220 V	220 V	220 V
Rated output 1	1,8 kW	1,8 kW	3,0 kW
Rated current 1	8,3 A	8,3 A	13,7 A
Fuse 1	10 A	10 A	16 A
Rated voltage 2	230 V	230 V	230 V
Rated output 2	2,0 kW	2,0 kW	3,3 kW
Rated current 2	8,7 A	8,7 A	14,3 A
Fuse 2	10 A	10 A	16 A
Rated voltage 3	240 V	240 V	240 V
Rated output 3	2,2 kW	2,2 kW	3,6 kW
Rated current 3	9,1 A	9,1 A	15 A
Fuse 3	10 A	10 A	16 A
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE	1/N/PE
Rated capacity	5 l	10 l	15 l
Power supply	1/N/PE	1/N/PE	1/N/PE
Standby energy consumption/24 h at 65 °C	0,2 kWh	0,3 kWh	0,37 kWh
Colour	white	white	white

<b>IP-Rating</b>	IP24 D	IP24 D	IP24 D
<b>Energy efficiency class</b>	A	A	A
<b>Weight</b>	3 kg	4,6 kg	6,1 kg

oversink water heater pack that comes complete with inlet valve and outlet spout

## **Contact information**

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

[sales@stiebel-eltron.co.uk](mailto:sales@stiebel-eltron.co.uk)

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.