



Main

Range	Thorsman
Range of product	Thorsman
Product or component type	Nail clip
Device short name	TC
Device application	Installation of round cable
Cable type	Round cable 5...7 mm
Type of installation	Indoor
Provided equipment	Nail
Nail diameter	2 mm
Length	25 mm
Embedding depth	17 mm

Complementary

Colour tint	Black (NCS 9500)
Material	Clip: PP (polypropylene) Nail: electroplated hardened steel
Atmospheric-corrosivity category	C2
Ambient air temperature for operation	-40...80 °C

Environment

Environmental characteristic	Impact resistant UV resistant
Quantity per set	Set of 100
Net weight	0.00085 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.2 cm
Package 1 Width	1.2 cm
Package 1 Length	2.5 cm
Package 1 Weight	0.85 g
Unit Type of Package 2	BAG
Number of Units in Package 2	100
Package 2 Height	8.8 cm
Package 2 Width	4 cm
Package 2 Length	5.8 cm
Package 2 Weight	96 g

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------