

## EMT 32

Membrane spout, TPE, RAL 7035, M32



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>Material</b>	Thermoplastic elastomer
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	80 °C
<b>Glow wire test</b>	750 °C
<b>Protection class</b>	IP66
<b>Ø Connection thread D</b>	32
<b>Length screw-in thread L</b>	9,5 mm
<b>Ø cable diameter min</b>	1 mm
<b>Ø cable diameter max</b>	25 mm
<b>External diameter ED</b>	37 mm
<b>Total length TL</b>	11 mm
<b>Ø Drilling</b>	32 mm - 33,2 mm
<b>Wall thickness S</b>	2 mm
<b>Product Color</b>	RAL 7035
<b>Order no. RAL 7035</b>	10062562
<b>Type</b>	EMT 32
<b>Packing unit</b>	100
<b>ETIM-Classification</b>	EC000451

13.08.2021

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:  
**WISKA Hoppmann GmbH**  
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany  
☎ +49-4191-508-0 · 📠 +49-4191-508-209  
contact@wiska.de · www.wiska.com

Other technical data on request / subject to change without notice