



SA-90 CONTACT SPRAY ADHESIVE

SA-90 heavy-duty multi-purpose contact spray adhesive is a superior adhesive with flexible repositioning capability, providing right first time results. Delivers a powerful, permanent bond with a very smooth and professional appearance. The aerosol ensures easy application easy with an adjustable spray pattern to help minimise overspray. Highly economical: coverage area approx. 3-5m².

KEY FEATURES

- Heavy duty multi-purpose contact spray adhesive
- Strong, flexible bond
- Easy to use with precise positioning capability
- Adjustable spray pattern minimises overspray
- Coverage approximately 3-5m²
- Non-chlorinated

NEVER ASK A PROFESSIONAL TO USE ANYTHING ELSE!

APPLICATION AREAS

Use SA-90 for bonding automotive upholstery, trim and foam backed carpet, carpet tiles, displaying signage, and paper/card. Suitable for use on all metals, wood, ceramic and cork.

DIRECTIONS FOR USE

- Surfaces to be bonded must be clean, dry and free from grease, dust, paint, polish and loose material.
- Shake the can well before use. SA-90 should be applied directly from the can onto both surfaces to be bonded.
- Spray from a distance of approximately 15cm covering both surfaces with an even coating.
- Allow the adhesive to dry slightly. This will take approximately 3 to 4 minutes at normal room temperature (the drying time will be longer at lower temperatures).
- When the surfaces are tack dry, press them together with firm even pressure.
- Very porous surfaces may require two coats of adhesive and drying time may be longer.
- After use, invert the can and spray a small amount of product to clear the nozzle.
- Store the product in a dry place at between 5°C and 25°C.

MARKET SECTORS:

- TRADE/PRO DIY
- AGRICULTURE
- ELECTRICAL MRO
- ENGINEERING
- FASTENERS & FIXINGS

AC CODE	CRC CODE	SIZE
1847	32806	500ml Aerosol

APPEARANCE:	Pale yellow, adhesive film
ODOUR:	Ketone solvent
SPECIFIC GRAVITY AT 20°C:	0.8
SOLUBILITY:	Insoluble in water
COVERAGE:	3 - 5 m ²

(All values apply to product without aerosol propellant)

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) is available from <https://www.actioncan.com/product/sa-90/> or from info.uk@crcind.com

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 3 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

MISREPRESENTATION ACT 1967 & TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. Should you have a technically complex enquiry, please email us for specialist/laboratory support.

