



Flush Magnetic Contact

Code: FC508/WH/MULTI/G3/EN

FC508 | Flush Contact | Grade 3 | White | Multi Resistor

This flush mounted magnetic door contact can be used in most intruder alarm systems up to and including grade 3 as specified in EN50131-1:2006 and is certified to EN50131-2-6:2008 and environmental class II (for use indoors) by Kiwa FSS. It has 4 terminals to allow for the selection of either double pole or EoL configuration and is suitable for use on double door applications, it is also protected against tampering by lid removal.

Features & Benefits

- Screw terminal block, no junction box required
- Microswitch tamper
- Selectable end of line resistor
- Can use own resistors
- Available in white or brown
- Can be fitted in double pole systems
- Can be used on double door configuration
- Magnetic Immunity



Product Information

Connection type	Terminal
-----------------	----------

Security

EN50131-2-6 Grade	3
Tamper Protection	Cover & MID

Environmental

EN50130-5 class	Class II
IP Rating	4X
Temperature range	-15°C - +40°C

Housing

Colour	White
Material	HIPS
Contact Dimensions (mm)	33 x 22 x 32
Magnet Dimensions (mm)	33 x 22 x 32

Electrical

Connection type	Terminal
No. of terminals	4 Screw
Contact type	Normally Closed
Contact Material	Silver Plated Copper

Features

Mode of operation	DP, EOL/FSL
Resistor Type	A, B, D, E & I
Operation Axes (X, Y, Z)	Y, Z
Pull-in gap (X, Y, Z)mm	4, 3
Suitable for Double Door	Yes
No. of terminals	4 Screw

