



## Roller Shutter Contact

*Code: RS002/ALI/G2/AB*

RS002 Type AB | Roller Shutter Contact | Grade 2 | Aluminium | Multi Resistor

This roller shutter contact can be used in most security systems up to and including grade 2 as specified in EN50131-1:2006+A3:2020 and is compliant with EN50131-2-6:2008 and environmental class III. The contact is potted/sealed to prevent access to the inside of the contact.

### Features & Benefits

- High Quality Alloy Finish
- Other resistor value available
- 45cm or 1 mtr Armoured cable lengths
- EN50131-2-6 Grade 2
- Environmental Class III



## Product Information

Connection type	Wired
-----------------	-------

## Security

EN50131-2-6 Grade	2
Tamper Protection	Internal

## Environmental

EN50130-5 class	Class III
IP Rating	32
Temperature range	-10°C - +40°C

## Housing

Colour	Aluminium
Material	Aluminium
Contact Dimensions (mm)	171 x 50 x 12
Magnet Dimensions (mm)	83 x 71 x 30

## Electrical

Connection type	Wired
No. of terminals	8 Wire
Contact type	Normally Closed
Contact Material	Ruthenium
Wire length (mm)	450

## Features

Mode of operation	DP, EOL/FSL
Resistor Type	A, B
Operation Axes (X, Y, Z)	X, Y
Pull-in gap (X, Y, Z)mm	25, 50
Suitable for Double Door	Yes
No. of terminals	8 Wire

