



Roller Shutter Contact


Code: RS007/G3/AB

RS007 Type AB | Roller Shutter Contact | Grade 3 | Aluminium | Multi Resistor

This roller shutter contact can be used in most security systems up to and including grade 3 as specified in EN50131-1:2006+A3:2020 and is compliant with EN50131-2-6:2008 and environmental class III. The contact is potted/sealed to prevent access to the inside of the contact.

Features & Benefits

- High Quality Alloy Finish
- Selectable (A,B)
- Other resistor value available
- Locating mechanism to aid alignment
- 45cm or 1 mtr Armoured cable lengths
- EN50131-2-6 Grade 3
- Environmental Class III



Product Information

Connection type	Wired
-----------------	-------

Security

EN50131-2-6 Grade	3
Tamper Protection	Internal & MID

Environmental

EN50130-5 class	Class III
IP Rating	42
Temperature range	-15°C - +40°C

Housing

Colour	Aluminium
Material	Aluminium
Contact Dimensions (mm)	170 x 50 x 14
Magnet Dimensions (mm)	83 x 86 x 32

Electrical

Connection type	Wired
No. of terminals	8 Wire
Contact type	Normally Closed
Contact Material	Rhodium & Ruthenium
Wire length (mm)	450

Features

Mode of operation	DP, EOL/FSL
Resistor Type	A, B
Operation Axes (X, Y, Z)	Y, Z
Pull-in gap (X, Y, Z)mm	23, 28
Suitable for Double Door	Yes
No. of terminals	8 Wire

