



Surface Magnetic Contact

Code: SC517/WH/MULTI/G2/EN

SC517 | Surface Contact | Grade 2 | White | Multi Resistor

This compact surface mounted magnetic contact can be used in most security systems up to and including grade 2 as specified in EN50131-1: 2006 and is certified to EN50131-2-6:2008 and environmental class II (for use indoors) by Kiwa FSS. This contact can be used on windows and doors to detect the unauthorised entry of an intruder. The contact is also tamper protected against removal from its mounting surface.

Features & Benefits

- 4 Terminals
- Microswitch tamper
- Selectable end of line resistor
- Can use own resistors
- Available in white or brown
- Can be fitted in double pole systems
- Can be used on double door configuration
- Contact spacers available



Product Information

Connection type	Wired
-----------------	-------

Security

EN50131-2-6 Grade	2
Tamper Protection	RFMS

Environmental

EN50130-5 class	Class II
IP Rating	3X
Temperature range	-15°C - +40°C

Housing

Colour	White
Material	HIPS
Contact Dimensions (mm)	65 x 13 x 13
Magnet Dimensions (mm)	65 x 13 x 13

Electrical

Connection type	Wired
No. of terminals	4 Terminals
Contact type	Normally Closed
Contact Material	Rhodium

Features

Mode of operation	DP, EOL/FSL
Resistor Type	A, B, D, E & I
Operation Axes (X, Y, Z)	X, Y
Pull-in gap (X, Y, Z)mm	25, 15
Suitable for Double Door	Yes
No. of terminals	4 Terminals

