

Surface Magnetic Contact

Code: SC570/WH/G2/EN

SC570 | Surface Contact | Grade 2 | White | Non-resistored



This magnetic door contact can be used in most security systems up to and including grade 2 and environmental class II as specified in EN50131-1 and is certified to EN50131-2-6 by Kiwa FSS. This contact can be used on windows and doors to detect the unauthorised entry of an intruder. The contact is also protected against tampering with optional detection of removal from its mounting surface.

Features & Benefits

- 6 Terminals
- Cover and wall tamper
- Available in white, brown or anthracite grey
- EN50131-2-6 Grade 2
- Environmental Class II



Product Information

Connection type	Wired
-----------------	-------

Security

EN50131-2-6 Grade	2
Tamper Protection	Cover & RFMS

Environmental

EN50130-5 class	Class II
IP Rating	3X
Temperature range	-15°C - +40°C

Housing

Colour	White
Material	HIPS
Contact Dimensions (mm)	85 x 25 x 21
Magnet Dimensions (mm)	85 x 25 x 21

Electrical

Connection type	Wired
No. of terminals	6 Terminal
Contact type	Normally Closed
Contact Material	Rhodium

Features

Mode of operation	DP
Operation Axes (X, Y, Z)	X, Y
Pull-in gap (X, Y, Z)mm	36, 27
Suitable for Double Door	Yes
No. of terminals	6 Terminal