



### Main

Range	Acti9
Product name	Load centre KQ II B
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Standard
Door type	Overall
Provided equipment	Enclosure Door Front cover Pan assembly Earth terminal block 25 mm <sup>2</sup> Shielded neutral bar 25 mm <sup>2</sup>
Colour	Grey (RAL 7035)

### Complementary

Enclosure mounting	Surface
[Ie] rated operational current	250 A at 400/415 V AC
Incomer device options	Lugs Switch disconnector - 4P Terminal block - 4P MCCB - 4P RCCB - 30 mA - 4P RCCB - 100 mA - 4P RCCB - 300 mA - 4P
Protection device options	Miniature circuit breaker (MCB) (plug-on type) as outgoer Residual current circuit breaker with overcurrent protection (RCBO) (plug-on type) as outgoer
Number of ways	24 ways (3P) outgoer
Cable entry	Top and bottom: knock-out Side: knock-out
Height	1024 mm
Width	470 mm
Depth	139 mm

### Environment

IP degree of protection	IP2x B internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529
-------------------------	--

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.0 cm
Package 1 Width	48.0 cm
Package 1 Length	103.0 cm
Package 1 Weight	19.2 kg
Unit Type of Package 2	P12
Number of Units in Package 2	10
Package 2 Height	112.0 cm
Package 2 Width	100.0 cm

Package 2 Length	120.0 cm
Package 2 Weight	207.0 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>