



Main

| | |
|-----------------------------|---|
| Circuit breaker application | Distribution |
| Range | Acti9 |
| Product name | Acti9 iC60 RCBO |
| Product or component type | Residual current breaker with overcurrent protection (RCBO) |
| Device short name | iC60N RCBO |
| Poles description | 1P + Ns |
| [In] rated current | 6 A at 30 °C |
| Curve code | B |
| Earth-leakage sensitivity | 30 mA |
| Breaking capacity | 10000 A Icn at 150...230 V AC 50 Hz |

Complementary

| | |
|--|---|
| Neutral position | Left |
| Number of protected poles | 1 |
| Network frequency | 50 Hz |
| Network type | AC |
| Trip unit technology | Thermal-magnetic |
| [Ue] rated operational voltage | 150...230 V AC 50 Hz |
| Residual current tripping technology | Voltage dependent |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type A |
| [Icw] rated short-time withstand current | Icw: 250 A during 8/20 µs impulse withstand |
| Electrical insulation class | Class III |
| Limitation class | 3 |
| [Ui] rated insulation voltage | 400 V AC 50 Hz |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Surge current | 250 A |
| Suitability for isolation | Yes |
| Contact position indicator | Yes |
| Control type | Toggle |
| Local signalling | ON/OFF indication |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Comb busbar and distribution block compatibility | YES |
| 9 mm pitches | 2 |
| Height | 117 mm |
| Width | 18 mm |
| Depth | 70 mm |
| Net weight | 136 g |
| Colour | White |
| Mechanical durability | 20000 cycles |
| Electrical durability | 10000 cycles |
| Provision for padlocking | Padlockable |
| Locking options description | By padlocks |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|--------------------------|--|
| Connections - terminals | Screw clamp terminal (upstream) 1...16 mm ² rigid Screw clamp terminal (upstream) 1...16 mm ² flexible Screw clamp terminal (downstream) 1...10 mm ² rigid Screw clamp terminal (downstream) 1...10 mm ² flexible |
| Wire stripping length | 14 Mm for upstream connection 11 mm for downstream connection |
| Tightening torque | 2 N.M upstream 2 N.m downstream |
| Earth-leakage protection | Integrated |
| Targeted country | UK |

Environment

| | |
|---------------------------------------|------------------------------|
| Standards | IEC 61009-1 IEC 61009-2-2 |
| Product certifications | SNI |
| IP degree of protection | IP20 |
| Tropicalisation | 2 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -25...55 °C |
| Ambient air temperature for storage | -30...70 °C |

Packing Units

| | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.800 cm |
| Package 1 Width | 11.200 cm |
| Package 1 Length | 14.000 cm |
| Package 1 Weight | 233.000 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 34 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 8.040 kg |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 544 |
| Package 3 Height | 75.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 60.000 cm |
| Package 3 Weight | 144.000 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |