



### Main

Range	Acti 9
Product name	Load centre KQ II A
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Standard
Door type	Overall
Provided equipment	Enclosure Door Front cover Pan assembly Earth terminal block 25 mm <sup>2</sup> Shielded neutral bar 25 mm <sup>2</sup>

### Complementary

Enclosure mounting	Surface
[I <sub>e</sub> ] rated operational current	125 A at 230/240 V AC
Incomer device options	Switch disconnecter - 2P Terminal block - 2P RCCB - 30 mA - 2P RCCB - 100 mA - 2P RCCB - 300 mA - 2P
Protection device options	Miniature circuit breaker (MCB) (plug-on type) as outgoer Residual current circuit breaker with overcurrent protection (RCBO) (plug-on type) as outgoer
Number of ways	12 ways (1P) outgoer
Cable entry	top and bottom: knock-out side: knock-out
Height	270 mm
Width	376 mm
Depth	127 mm

## Environment

IP degree of protection	IP2x B internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529
-------------------------	--

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------