SE250SW3L

LoadCentre KQ - switch disconnector - 250A - 3P+N for type B distribution board



| Main | |
|---------------------------|---------------------|
| Range | Acti9 |
| Product or component type | Switch disconnector |
| Device application | Protection |

Complementary

| Complementary | |
|----------------------------------|--------------------|
| [le] rated operational current | 250 A at 415 V |
| Poles description | 3P + N |
| Product destination | Distribution board |
| Suitable for cable cross section | 185 mm² |

Environment

| Standards BS EN 60947-3 | | |
|-------------------------|-----------|---------------|
| | Standards | BS EN 60947-3 |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|-----------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 20.0 cm | |
| Package 1 Width | 48.0 cm | |
| Package 1 Length | 51.0 cm | |
| Package 1 Weight | 11.53 kg | |
| Unit Type of Package 2 | P12 | |
| Number of Units in Package 2 | 16 | |
| Package 2 Height | 112.0 cm | |
| Package 2 Width | 100.0 cm | |
| Package 2 Length | 120.0 cm | |
| Package 2 Weight | 204.48 kg | |

Offer Sustainability

| REACh Regulation | REACh Declaration |
|----------------------------|---|
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | €Yes |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |