SEA9BN8

Acti9 Isobar B - distribution board -250A-400/415 V - 8 ways - IP31 - RAL 9001





Main Range Acti9 Product name Acti9 Isobar B Product or component Distribution board type Device application Distribution Standard Enclosure type Earth stud Provided equipment Enclosure Door Front cover Pan assembly Neutral terminal block Earth terminal block Removable gland plates

Blanking plate

Cream (RAL 9001)

Complementary

Enclosure mounting	Surface
Poles description	3P + N
[le] rated operational current	250 A at 400/415 V AC 250 A at 230/240 V AC
Breaking capacity	25 kA
Overvoltage category	IV
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Incomer device options	Switch disconnector - 3P + N Switch disconnector - 4P MCCB - 4P Terminal block - 4P Contactor - 4P RCCB - 4P
Protection device options	Miniature circuit breaker (MCB) in outgoer Residual current circuit breaker with overcurrent protection (RCBO) in outgoer
Number of ways	8 ways (3P) outgoer
Enclosure material	Steel
Surface treatment	Ероху
Surface finish	Powder paint
Height	538 mm
Width	470 mm
Depth	138 mm
Net weight	11 kg

Colour

Environment

Standards	BS EN 61439-3	
IP degree of protection	IP2X without cover internal conforming to BS EN 60529 IP3x with cover external conforming to BS EN 60529	
IK degree of protection	IK05	
Ambient air temperature for operation	-3570 °C	
Ambient air temperature for storage	-4080 °C	

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.3 cm
Package 1 Width	47.0 cm
Package 1 Length	54.5 cm
Package 1 Weight	11.233 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	24
Package 2 Height	112.0 cm
Package 2 Width	100.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	284.592 kg

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
Halogen content performance	Halogen free plastic parts product