



### Main

|                           |                |
|---------------------------|----------------|
| Range                     | Acti9          |
| Product or component type | Terminal block |
| Device application        | Connection     |

### Complementary

|  |  |
|--|--|
| Range compatibility                    | Acti 9 Acti9 DB TNA chassis<br>Acti 9 Acti9 DB PEV chassis |
| [Ie] rated operational current         | 125 A  |
| [Ui] rated insulation voltage          | 500 V  |
| Poles description                      | 1P   |
| [Uimp] rated impulse withstand voltage | 6 kV   |
| Width                                  | 18 mm  |
| Cable stiffness                        | Flexible 35 mm <sup>2</sup><br>Solid 50 mm <sup>2</sup>    |
| Ambient air temperature for storage    | -40...85 °C  |

### Packing Units

|                              |            |
|------------------------------|------------|
| Unit Type of Package 1       | PCE        |
| Number of Units in Package 1 | 1          |
| Package 1 Height             | 2.000 cm   |
| Package 1 Width              | 7.000 cm   |
| Package 1 Length             | 9.000 cm   |
| Package 1 Weight             | 77.500 g   |
| Unit Type of Package 2       | S02        |
| Number of Units in Package 2 | 52         |
| Package 2 Height             | 15.000 cm  |
| Package 2 Width              | 30.000 cm  |
| Package 2 Length             | 40.000 cm  |
| Package 2 Weight             | 4.290 kg   |
| Unit Type of Package 3       | P12        |
| Number of Units in Package 3 | 832        |
| Package 3 Height             | 45.000 cm  |
| Package 3 Width              | 80.000 cm  |
| Package 3 Length             | 120.000 cm |
| Package 3 Weight             | 80.640 kg  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                             |  |
|-----------------------------|--|
| Sustainable offer status    | Green Premium product                                      |
| REACH Regulation            | <a href="#">REACH Declaration</a>                          |
| EU RoHS Directive           | Pro-active compliance (Product out of EU RoHS legal scope) |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>                     |
| RoHS exemption information  | <a href="#">Yes</a>  |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>              |
| Circularity Profile         | No need of specific recycling operations                   |
| Halogen content performance | Halogen free plastic parts product                         |