

Product Code: OA411AG

Description: 1 Gang 2 Way IP66 Weatherproof Switch Unit



General Information

Dimensions	91mm (W) x 106mm (H) x 72.5mm (D)
External Finish	Anthracite Grey
Materials	Cover, Housing & Clip: Polycarbonate Seal & Gasket: Rubber Switch Membrane: Neoprene Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass
Maximum Voltage	250V~ 50Hz
Load Rating	10AX (Suitable for Inductive Loads)
Terminal Size	3.5mmØ
Terminal Torque	0.4Nm
Terminal Capacity	4 x 1.5mm ² or 2 x 2.5mm ²
Two Way	Yes
Ingress Protection	IP66
Termination Type	Screw
Back Box Knockouts	5 x 20mmØ
Operational Temperature	-5°C to +40°C
Warranty	5 Years
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008 BS EN 60529: 2011 (Sections 13 & 14)

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Interchangeable with 13A/10AX modules in the MiniGrid Range.

